

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No:
MEDB000009C
Revision No:
2

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV GL AS under the authority of the Government of Norway.

This is to certify:

That the A & B Class divisions fire integrity: B class divisions.

with type designation(s)
BIP CAH-35: B-15 Class Access Hatch

Issued to

BIP Industires Co., Ltd. Goseong
Goseong-gun, Gyeongsangnam-do, Republic of Korea

is found to comply with the requirements in the following Regulations/Standards:

Regulation **(EU) 2020/1170,**

item No. MED/3.11b. SOLAS 74 as amended, Regulation II-2/3.4 & II-2/9, IMO 2010 FTP Code, IMO MSC/Circ.1120 and IMO MSC.1/Circ.1581


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2025-11-15.**

Issued at **Høvik** on **2020-11-16**

DNV GL local station:
Gimhae Station

Approval Engineer:
Karolina Kusmider



Notified Body
No.: **0575**

for **DNV GL AS**

Roald Vårheim
Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005, and amended by Decision No 1/2019 dated February 22nd, 2019.

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.



LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV GL AS, its parent companies and subsidiaries as well as their officers, directors and employees ("DNV GL") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Job Id: **344.1-004909-5**
Certificate No: **MEDB000009C**
Revision No: **2**

Product description

"BIP CAH-35: B-15 Class Access Hatch"

a ceiling access hatch composed of a hinged single hatch leaf with hatch frame and locking arrangement. The hatch leaf is composed of a 33.5 mm thick insulation core of mineral wool with nominal density 140 kg/m³ (from KCC Corporation, Korea), covered on each side with 0.6 mm thick steel sheets. The hatch frame is composed of 1.6 mm thick folded steel plates that are screwed to the ceiling (via support channels).

The hatch is attached to the frame with a stainless-steel piano hinge and locked in position with a 3-way locking device.

For further details, see the drawings listed under Type Examination documentation below.

Application/Limitation

Approved for use as an integrated part of a horizontal fire retarding division of class B-15.

Approved for installation in the tested ceiling type BIP C-162 from BIP Industires Co., Ltd. Goseong. Installation in other ceilings may be approved case-by-case. Ceiling has to be approved according to the Marine Equipment Directive and bear the Mark of Conformity.

Max. size of hatch: 890 x 790 mm (W x L)

Max. hatch clear opening: 800 x 700 mm (W x L)

The insulation materials and adhesives used have to be approved according to the Marine Equipment Directive and bear the Mark of Conformity. This requirement may also be applicable for surface materials used, if required by relevant rules and regulations.

Each product is to be supplied with its manual for installation and use.

Type Examination documentation

Test Report No. AK2015-0434 dated 05 August 2015 from Fire Insurers Laboratories of Korea (FILK), Korea.

Drawing No. F2015-CAH35-R0 (8 pages) dated 15 June 2015 from Manufacturer.

Tests carried out

Tested according to IMO 2010 FTP Code part 3.

Marking of product

The product is to be marked with name and address of manufacturer, type designation, fire technical rating, the MED Mark of Conformity and USCG Approval Number if applicable (see first page).