

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No: MEDB00001DX Revision No:

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV AS under the authority of the Government of Norway.

This is to certify:

That the A & B Class divisions fire integrity: B class divisions.

with type designation(s)

BIP D-163: B-15 Class Bulkhead

Issued to

BIP Industries Co., Ltd. Goseong Goseong-gun, Gyeongsangnam-do, Republic of Korea

is found to comply with the requirements in the following Regulations/Standards: Regulation (EU) 2022/1157,

item No. MED/3.11b. SOLAS 74 as amended, Regulation II-2/3.4 & II-2/9, IMO 2010 FTP Code, IMO MSC/Circ.1120 and IMO MSC.1/Circ.1581

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until 2027-11-12.

Issued at Høvik on 2022-11-13

DNV local station: **Gimhae Station**

Approval Engineer: Izabela Misztal

0

Notified Body No.: **0575** for **DNV AS**

Sverre Olav Bergli Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005, and amended by Decision No 1/2019 dated February 22nd, 2019.



The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU. This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Form code: MED 201.NOR Revision: 2022-02 www.dnv.com Page 1 of 2



Job Id: **344.1-003068-13** Certificate No: **MEDB00001DX**

Revision No: 3

Product description

"BIP D-163: B-15 Class Bulkhead"

Consist of two insulated steel panels mounted with a 20 mm air gap between them. Each panel is made of 15 mm thick mineral wool (from KCC Corporation, Korea) of 200 kg/m³ nominal density, bonded with an adhesive to a 0.6 mm galvanized steel plate on one side. Steel plates on the panels are facing outer side, while the uncovered mineral wool is facing inside of the bulkhead. The panels are fitted together with Z-shaped fixing cleats and screws.

The inside panel is put on the base with fitting screw and the outside panel is having a cable conduit way. The 3.2 mm thickness "base plate" is fitted in the lower part of the panel on the exposed side and mounted by fitting screws.

Total bulkhead thickness is 50 mm.

For further details, see approved drawings / Test Reports listed under Type Examination documentation below.

Application/Limitation

Approved for use as a vertical fire retarding division of class B-15.

Max panel size: 600 x 2480 mm (width x height).

The insulation materials and adhesives used have to be approved according to the Marine Equipment Directive and bear the Mark of Conformity. This requirement may also be applicable for surface materials used, if required by relevant rules and regulations.

Each product is to be supplied with its manual for installation and maintenance.

Type Examination documentation

Test report No. AK2016-0173 dated 6 April 2016 from Fire Insurers Laboratories of Korea (FILK), Gyeonggi-do, Korea. Test report No. AK2022-0307 dated 15 September 2022 from Fire Insurers Laboratories of Korea (FILK), Gyeonggi-do, Korea.

Drawing No. F2016-D163-R0 (6 Pages) dated 1 February 2016 from manufacturer. Drawing No. F2022-D163-R0 (6 Pages) dated 17 June 2022 from manufacturer.

Tests carried out

Tested according to IMO 2010 FTP Code part 3.

Marking of product

The product is to be marked with name and address of manufacturer, type designation, fire technical rating, MED Mark of Conformity and USCG approval number if applicable (see first page).

Form code: MED 201.NOR Revision: 2022-02 www.dnv.com Page 2 of 2