

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No: **MEDB00001DY** Revision No:

4

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV AS under the authority of the Government of Norway.

This is to certify:

That the A & B Class divisions fire integrity: B class divisions.

with type designation(s)

BIP W-302 & BIP W-302E: B-15 Class Bulkheads

Issued to

BIP Industries Co., Ltd. Goseong Goseong-gun, Gyeongsangnam-do, Republic of Korea

is found to comply with the requirements in the following Regulations/Standards: Regulation (EU) 2021/1158,

item No. MED/3.11b. SOLAS 74 as amended, Regulation II-2/3.4 & II-2/9, IMO 2010 FTP Code, IMO MSC/Circ.1120 and IMO MSC.1/Circ.1581

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until 2027-01-30.

Issued at Høvik on 2022-01-31

DNV local station: **Gimhae Station**

Approval Engineer: Marcin Tobiasz

0

Notified Body No.: **0575** for **DNV AS**

Sverre Olav Bergli Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005, and amended by Decision No 1/2019 dated February 22nd, 2019.



The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU. This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Form code: MED 201.NOR Revision: 2021-03 www.dnv.com Page 1 of 2



Job Id: **344.1-003282-10** Certificate No: **MEDB00001DY**

Revision No: 4

Product description

"BIP W-302: B-15 Class Bulkhead"

consists of 48.5 mm thick mineral wool core (from KCC Corporation) with nominal of density of 140 kg/m³ faced on the outer sides with 0.6 mm galvanized steel sheets.

BIP W-302E: B-15 Class Bulkhead"

consists of 47.7 mm thick mineral wool core (from KCC Corporation) with nominal of density of 140 kg/m³ and 30 mm wide mineral wool strips on the sides of the panel with nominal density of 240 kg/m³. Panel is faced by means of adhesive with outer 0.6 mm galvanized steel sheets + inner 0.4 mm perforated (max. φ =4.0 mm, pitch 8.5 mm) steel sheets. Panel is equipped with internal cable conduit way with dimensions 50 mm x 20 mm (B x W).

Panels thickness is 50 mm.

Panels are connected to each other by removable cap profiles on both panel sides.

For further details see approved drawings listed under Type Examination documentation below.

Application/Limitation

Approved for use as a vertical fire retarding division of class B-15.

Max. panel size:

- 550 x 2480 mm (W x H) for panels BIP W-302
- 550 x 2480 mm (W x H) for panels BIP W-302E

The insulation materials and adhesives used have to be approved according to the Marine Equipment Directive and bear the Mark of Conformity. This requirement may also be applicable for surface materials used, if required by relevant rules and regulations.

Each product is to be supplied with its manual for installation and maintenance.

Type Examination documentation

Test report No. AK2013-0237 dated 4 November 2013 from Fire Insurers Laboratories of Korea (FILK), Gyeonggi-Do, Korea

Test report No. AK2016-0404 dated 8 July 2016 from Fire Insurers Laboratories of Korea (FILK), Gyeonggi-Do, Korea.

Drawing No. F2013-W302-R0 (5 pages) dated 30 July 2013 from manufacturer.

Drawing No. F2016-W302E-R0 (8 pages) dated 13 May 2016 from manufacturer.

Tests carried out

Tested according to IMO 2010 FTP Code part 3.

Marking of product

The product is to be marked with name and address of manufacturer, type designation, fire technical rating, MED Mark of Conformity and USCG approval number if applicable (see first page).

Form code: MED 201.NOR Revision: 2021-03 www.dnv.com Page 2 of 2