

# EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate no.: MEDB000062D Revision No: 2

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV AS under the authority of the Government of Norway.

#### This is to certify:

that the A & B Class divisions fire integrity: B class divisions.

with type designation(s) BIP W-302SE / B-15 Class Bulkhead

## <sup>issued to</sup> BIP Industries Co., Ltd. Goseong Goseong-gun, Gyeongsangnam-do, Korea, Republic of

is found to comply with the requirements in the following Regulations/Standards: Regulation (EU) 2024/1975, item No. MED/3.11b. SOLAS 74 as amended, Regulation II-2/3.4 & II-2/9, IMO 2010 FTP Code, IMO MSC/Circ.1120 and IMO MSC.1/Circ.1581

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until 2029-11-04.

Issued at Høvik on 2024-11-05

DNV local unit: Gimhae Station

Approval Engineer: Timo Linn



Notified Body No.: 0575

for DNV AS

Digitally Signed By: Christine Mydlak-Röder Location: DNV Høvik, Norway

Mydlak-Röder, Christine Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005, and amended by Decision No 1/2023 dated August 21st, 2023. The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the



production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU. This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV AS of any changes to the approved orguing the product of the approved type. The manufacturer shall inform DNV AS of any changes to the approved

AN THE

equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled. Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Form code: MED 201.NOR



Job ID: 34 Certificate no.: MI Revision No: 2

344.1-004545-4 MEDB000062D 2

#### **Product description**

"BIP W-302SE / B-15 Class Bulkhead"

composed of panels faced on both sides with 0.6 mm thick galvanized + 0.4 mm thick perforated steel sheets and insulated with 2 x 25 mm thick mineral wool of density 140 kg/m<sup>3</sup> (manufactured by KCC Corporation). Between the insulation in the middle it is an air gap of 5 mm. On each side of the joints, in a length of 50 mm, the panels are insulated with the same type of insulation as described above but with density 240 kg/m<sup>3</sup>, and without an air gap.

The mineral wool is glued to the steel sheets with an adhesive.

The panels are connected with a cap profile joint.

Total bulkhead panel thickness is 50 mm.

For further details see drawings listed under Type Examination documentation below.

## **Application/Limitation**

Approved for use as a vertical fire retarding division of class B-15.

Max. panel size is 540 mm x 2480 mm (W x H).

The insulation materials and adhesives used have to be approved according to the Marine Equipment Directive and bear the Mark of Conformity. This requirement may also be applicable for surface materials used, if required by relevant rules and regulations.

Each product is to be supplied with its manual for installation and maintenance.

## Type Examination documentation

Test Report No. AK2014-0070, dated 11 April 2014, from FILK, Korea.

Drawing No. F2014-W302SE-RO, dated 29 January 2014 from the manufacturer.

## Tests carried out

Tested according to IMO 2010 FTP Code Part 3.

## Marking of product

The product is to be marked with name and address of manufacturer, type designation, fire technical rating, MED Mark of Conformity and USCG approval number if applicable (see first page).